

Package: presentifyr (via r-universe)

July 15, 2026

Title PowerPoint Precision, Shiny Simplicity
Version 0.3.1
Description Create reproducible slideshows with PowerPoint and R.
License GPL (>= 3)
Encoding UTF-8
Roxygen list(markdown = TRUE)
RoxygenNote 7.3.3
Depends R (>= 2.10)
Imports bslib (>= 0.10.0), cli, jsonlite, fs (>= 1.6.4), pyro, here (>= 1.0.1), htmltools, jsTreeR (>= 2.6.0), log4r, pkglite (>= 0.2.2), rlang, yaml, shiny (>= 1.8.1.1), stats
Suggests mockery (>= 0.4.4), testthat (>= 3.0.0), withr
Config/testthat/edition 3
LazyData true
Config/pak/sysreqs cmake git make libuv1-dev zlib1g-dev
Repository <https://a2-ai.r-universe.dev>
Date/Publication 2026-06-04 20:46:24 UTC
RemoteUrl <https://github.com/a2-ai/presentifyr>
RemoteRef HEAD
RemoteSha cc25f1c7c1ecd974c84d4de38a683e41db117530

Contents

app	2
get_project_dir	2
initialize_app	2
toggle_logger	3
Index	4

app	<i>This function launches the Shiny application.</i>
-----	--

Description

This function launches the Shiny application.

Usage

```
app()
```

Value

This function does not return; it runs the Shiny app until the session is ended.

get_project_dir	<i>Get Project Root</i>
-----------------	-------------------------

Description

Returns the directory of the current project

Usage

```
get_project_dir()
```

Value

Project directory

initialize_app	<i>Initialize presentifyr Application Environment</i>
----------------	---

Description

Bootstraps the Python environment presentifyr's Shiny app needs by calling `pyro::initialize_python(groups = "presentifyr")`. This installs uv (if missing) and additively syncs the presentifyr dependency group (python-pptx, pillow) into `.venv/` from the pyro-bundled lockfile. The sync runs in `--inexact` mode, so any packages already present in the venv from prior fyr-package installs are left in place.

`uv sync --frozen --inexact --group presentifyr` is idempotent — it creates the venv if missing, installs the group if absent, and is a fast no-op if everything is already in place. Re-running this function is therefore safe and cheap.

Usage

```
initialize_app(verbose = TRUE)
```

Arguments

verbose Logical. Print initialization messages. Default TRUE.

Value

Invisibly a list:

- success: Logical. TRUE iff pyro returned without error.
- errors: Character vector of any error detail captured.

Examples

```
## Not run:
initialize_app()

## End(Not run)
```

toggle_logger

Updates the logging level for functions. Default is set to WARN

Description

Updates the logging level for functions. Default is set to WARN

Usage

```
toggle_logger()
```

Value

Called for its side effect of updating the logger in `.le$logger`. Returns NULL invisibly.

Examples

```
## Not run:
Sys.setenv("PRFY_VERBOSE" = "DEBUG")
toggle_logger()

## End(Not run)
```

Index

`app`, [2](#)

`get_project_dir`, [2](#)

`initialize_app`, [2](#)

`toggle_logger`, [3](#)